

Package ‘Familia’

August 24, 2026

Title 'shiny' Application for Population Structure and Ancestry Assessments

Version 2.0.0

Description Provides a 'shiny' web application developed by the Breeding Insight team to support pedigree validation and ancestry assessment of plant and animal populations. The app integrates Mendelian error analysis, parentage assignment and genetic composition/ancestry methods to help researchers evaluate genomic relationships through an accessible, web-based interface without requiring command-line tools. Pedigree validation, Mendelian error analysis and parentage assignment build on the 'BIGpopA' package (<https://CRAN.R-project.org/package=BIGpopA>) and support diploid and polyploid data. Ancestry estimation uses the sparse non-negative matrix factorization method of Frichot et al. (2014) [doi:10.1534/genetics.113.160572](https://doi.org/10.1534/genetics.113.160572) as implemented in the 'LEA' package by Frichot and Francois (2015) [doi:10.1111/2041-210X.12382](https://doi.org/10.1111/2041-210X.12382). Line and breed composition are estimated using the breed composition regression method of Funkhouser et al. (2017) [doi:10.2527/tas2016.0003](https://doi.org/10.2527/tas2016.0003), extended to polyploid species by Sandercock et al. (2025) [doi:10.1002/tpg2.70067](https://doi.org/10.1002/tpg2.70067).

License Apache License (>= 2)

URL <https://github.com/Breeding-Insight/Familia>

BugReports <https://github.com/Breeding-Insight/Familia/issues>

Encoding UTF-8

Depends R (>= 4.4.0)

Imports BIGpopA (>= 2.0.0), bs4Dash, config, curl, data.table, dplyr, DT, ggplot2, golem, httr, openxlsx, RColorBrewer, scales, shiny, shinydisconnect, shinyjs, shinyWidgets, tibble, tidyr, vcfR (>= 1.15.0), withr, zip

Suggests LEA, spelling, testthat

Language en-US

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Josue Chinchilla-Vargas [aut, cre],
Alexander M. Sandercock [aut],
Breeding Insight Team [aut]
Maintainer Josue Chinchilla-Vargas <josue.chinchilla@ufl.edu>
Repository CRAN
Date/Publication 2026-08-24 15:50:11 UTC

Contents

run_app	2
Index	4

run_app	<i>Run the Shiny Application</i>
---------	----------------------------------

Description

Run the Shiny Application

Usage

```
run_app(  
  onStart = NULL,  
  options = list(),  
  enableBookmarking = NULL,  
  uiPattern = "/",  
  ...  
)
```

Arguments

- | | |
|-------------------|---|
| onStart | A function that will be called before the app is actually run. This is only needed for shinyAppObj, since in the shinyAppDir case, a global.R file can be used for this purpose. |
| options | Named options that should be passed to the runApp call (these can be any of the following: "port", "launch.browser", "host", "quiet", "display.mode" and "test.mode"). You can also specify width and height parameters which provide a hint to the embedding environment about the ideal height/width for the app. |
| enableBookmarking | Can be one of "url", "server", or "disable". The default value, NULL, will respect the setting from any previous calls to enableBookmarking() . See enableBookmarking() for more information on bookmarking your app. |

<code>uiPattern</code>	A regular expression that will be applied to each GET request to determine whether the <code>ui</code> should be used to handle the request. Note that the entire request path must match the regular expression in order for the match to be considered successful.
<code>...</code>	arguments to pass to <code>golem_opts</code> . See <code>?golem::get_golem_options</code> for more details.

Value

A Shiny application object (of class `shiny.appobj`), invoked for the side effect of launching the Familia app.

Examples

```
if(interactive()){  
  run_app()  
}
```

Index

`enableBookmarking()`, [2](#)

`run_app`, [2](#)