

# Package ‘dfms’

January 26, 2026

**Version** 1.0.0

**Title** Dynamic Factor Models

**Description** Efficient estimation of Dynamic Factor Models using the Expectation Maximization (EM) algorithm or Two-Step (2S) estimation, supporting datasets with missing data and mixed-frequency nowcasting applications. Factors follow a stationary VAR process of order  $p$ . Estimation options include: running the Kalman Filter and Smoother once with PCA initial values (2S) as in Doz, Giannone and Reichlin (2011) [<doi:10.1016/j.jeconom.2011.02.012>](https://doi.org/10.1016/j.jeconom.2011.02.012); iterated Kalman Filtering and Smoothing until EM convergence as in Doz, Giannone and Reichlin (2012) [<doi:10.1162/REST\\_a\\_00225>](https://doi.org/10.1162/REST_a_00225); or the adapted EM algorithm of Banbura and Modugno (2014) [<doi:10.1002/jae.2306>](https://doi.org/10.1002/jae.2306), allowing arbitrary missing-data patterns and monthly-quarterly mixed-frequency datasets. The implementation uses the 'Armadillo' 'C++' library and the 'collapse' package for fast estimation. A comprehensive set of methods supports interpretation and visualization, forecasting, and decomposition of the 'news' content of macroeconomic data releases following Banbura and Modugno (2014). Information criteria to choose the number of factors are also provided, following Bai and Ng (2002) [<doi:10.1111/1468-0262.00273>](https://doi.org/10.1111/1468-0262.00273).

**URL** <https://docs.ropensci.org/dfms/>, <https://github.com/ropensci/dfms>

**BugReports** <https://github.com/ropensci/dfms/issues>

**Depends** R (>= 4.1.0)

**Imports** Rcpp (>= 1.0.1), collapse (>= 2.0.0)

**LinkingTo** Rcpp, RcppArmadillo

**Suggests** xts, vars, magrittr, testthat (>= 3.0.0), knitr, rmarkdown, covr

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.3.2

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**NeedsCompilation** yes

**Author** Sebastian Krantz [aut, cre],  
 Rytis Bagdziunas [aut],  
 Santtu Tikka [rev],  
 Eli Holmes [rev]

**Maintainer** Sebastian Krantz <sebastian.krantz@graduateinstitute.ch>

**Repository** CRAN

**Date/Publication** 2026-01-26 15:50:02 UTC

## Contents

dfms-package	2
.VAR	4
ainv	5
as.data.frame.dfm	6
BM14_Models	7
DFM	8
em_converged	15
FIS	16
ICr	17
news	19
plot.dfm	22
predict.dfm	24
residuals.dfm	27
SKF	29
SKFS	30
summary.dfm	32
tsnarmimp	33

  

<b>Index</b>	<b>35</b>
--------------	-----------

**Description**

*dfms* provides efficient estimation of Dynamic Factor Models via the EM Algorithm — following Doz, Giannone & Reichlin (2011, 2012) and Banbura & Modugno (2014). Contents:

**Information Criteria to Determine the Number of Factors**

`ICr()`

- `plot(<ICr>)`
- `screeplot(<ICr>)`

**Fit a Dynamic Factor Model**

`DFM()`

- `summary(<dfm>)`
- `plot(<dfm>)`
- `as.data.frame(<dfm>)`
- `residuals(<dfm>)`
- `fitted(<dfm>)`

**Generate Forecasts**

`predict(<dfm>)`

- `plot(<dfm_forecast>)`
- `as.data.frame(<dfm_forecast>)`

**News Decomposition**

`news(<dfm>)`

- `as.data.frame(<dfm_news_list>)`

**Fast Stationary Kalman Filtering and Smoothing**

`SKF()` — Stationary Kalman Filter

`FIS()` — Fixed Interval Smoother

`SKFS()` — Stationary Kalman Filter + Smoother

## Helper Functions

- .VAR() — (Fast) Barebones Vector-Autoregression
- ainv() — Armadillo's Inverse Function
- apinv() — Armadillo's Pseudo-Inverse Function
- tsnarmimp() — Remove and Impute Missing Values in a Multivariate Time Series
- em\_converged() — Convergence Test for EM-Algorithm

## Data

- BM14\_M — Monthly Series by Banbura and Modugno (2014)
- BM14\_Q — Quarterly Series by Banbura and Modugno (2014)
- BM14\_Models — Series Metadata + Small/Medium/Large Model Specifications

## References

- Doz, C., Giannone, D., & Reichlin, L. (2011). A two-step estimator for large approximate dynamic factor models based on Kalman filtering. *Journal of Econometrics*, 164(1), 188-205. [doi:10.1016/j.jeconom.2011.02.012](https://doi.org/10.1016/j.jeconom.2011.02.012)
- Doz, C., Giannone, D., & Reichlin, L. (2012). A quasi-maximum likelihood approach for large, approximate dynamic factor models. *Review of Economics and Statistics*, 94(4), 1014-1024. [doi:10.1162/REST\\_a\\_00225](https://doi.org/10.1162/REST_a_00225)
- Banbura, M., & Modugno, M. (2014). Maximum likelihood estimation of factor models on datasets with arbitrary pattern of missing data. *Journal of Applied Econometrics*, 29(1), 133-160. [doi:10.1002/jae.2306](https://doi.org/10.1002/jae.2306)

---

.VAR

*(Fast) Barebones Vector-Autoregression*

---

## Description

Quickly estimate a VAR(p) model using Armadillo's inverse function.

## Usage

.VAR(x, p = 1L)

## Arguments

- x data numeric matrix with time series in columns - without missing values.
- p positive integer. The lag order of the VAR.

**Value**

A list containing matrices  $Y = x[-(1:p), ]$ ,  $X$  which contains lags  $1 - p$  of  $x$  combined column-wise,  $A$  which is the  $np \times n$  transition matrix, where  $n$  is the number of series in  $x$ , and the VAR residual matrix  $res = Y - X \%*% A$ .

A list with the following elements:

Y	$x[-(1:p), ]$ .
X	lags $1 - p$ of $x$ combined column-wise.
A	$np \times n$ transition matrix, where $n$ is the number of series in $x$ .
res	VAR residual matrix: $Y - X \%*% A$ .

**See Also**

[dfms-package](#)

**Examples**

```
var = .VAR(diff(EuStockMarkets), 3)
str(var)
var$A
rm(var)
```

---

ainv

*Armadillo's Inverse Functions*

---

**Description**

Matrix inverse and pseudo-inverse by the Armadillo C++ library.

**Usage**

```
ainv(x)
apinv(x)
```

**Arguments**

x a numeric matrix, must be square for ainv.

**Value**

The matrix-inverse or pseudo-inverse.

**See Also**

[dfms-package](#)

## Examples

```
ainv(crossprod(diff(EuStockMarkets)))
```

---

as.data.frame.dfm	<i>Extract Factor Estimates in a Data Frame</i>
-------------------	---

---

## Description

Extract Factor Estimates in a Data Frame

## Usage

```
## S3 method for class 'dfm'
as.data.frame(
  x,
  ...,
  method = "all",
  pivot = c("long", "wide.factor", "wide.method", "wide", "t.wide"),
  time = seq_row(x$F_pca),
  stringsAsFactors = TRUE
)
```

## Arguments

x	an object class 'dfm'.
...	not used.
method	character. The factor estimates to use: any of "qml", "2s", "pca" (multiple can be supplied) or "all" for all estimates.
pivot	character. The orientation of the frame: "long", "wide.factor" or "wide.method", "wide" or "t.wide".
time	a vector identifying the time dimension, or NULL to omit a time variable.
stringsAsFactors	make factors from method and factor identifiers. Same as option to <a href="#">as.data.frame.table</a> .

## Value

A data frame of factor estimates.

## See Also

[dfms-package](#)

## Examples

```

library(xts)
# Fit DFM with 3 factors and 3 lags in the transition equation
mod <- DFM(diff(BM14_M), r = 3, p = 3)

# Taking a single estimate:
print(head(as.data.frame(mod, method = "qml")))
print(head(as.data.frame(mod, method = "qml", pivot = "wide")))

# Adding a proper time variable
time <- index(BM14_M)[-1L]
print(head(as.data.frame(mod, method = "qml", time = time)))

# All estimates: different pivoting methods
for (pv in c("long", "wide.factor", "wide.method", "wide", "t.wide")) {
  cat("\npivot = ", pv, "\n")
  print(head(as.data.frame(mod, pivot = pv, time = time), 3))
}

```

---

## Description

A data extract from BM 2014 replication files. Some proprietary series (mostly PMI's) are excluded. The dataset `BM14_Models` provides information about all series and their inclusion in the 'small', 'medium' and 'large' sized dynamic factor models estimated by BM 2014. The actual data is contained in `xts` format in `BM14_M` for monthly data and `BM14_Q` for quarterly data.

## Usage

```

BM14_Models
BM14_M
BM14_Q

```

## Format

`BM14_Models` is a data frame with 101 obs. (series) and 8 columns:

**series** BM14 series code (converted to snake case for R)

**label** BM14 series label

**code** original series code from data source

**freq** series frequency

**log\_trans** logical indicating whether the series was transformed by the natural log before differencing. Note that all data are provided in untransformed levels, and all data was (log-)differenced by BM14 before estimation.

**small** logical indicating series included in the 'small' model of BM14. Proprietary series are excluded.

**medium** logical indicating series included in the 'medium' model of BM14. Proprietary series are excluded.

**large** logical indicating series included in the 'large' model of BM14. This comprises all series, thus the variable is redundant but included for completeness. Proprietary series are excluded.

## Source

Banbura, M., & Modugno, M. (2014). Maximum likelihood estimation of factor models on datasets with arbitrary pattern of missing data. *Journal of Applied Econometrics*, 29(1), 133-160.

## See Also

[dfms-package](#)

## Examples

```
library(magrittr)
library(xts)

# Constructing the database for the large model
BM14 = merge(BM14_M, BM14_Q)
BM14[, BM14_Models$log_trans] %>% log()
BM14[, BM14_Models$freq == "M"] %>% diff()
BM14[, BM14_Models$freq == "Q"] %>% diff(3)

# Small Model Database
head(BM14[, BM14_Models$small])

# Medium-Sized Model Database
head(BM14[, BM14_Models$medium])
```

---

## Description

Efficient estimation of a Dynamic Factor Model via the EM Algorithm - on stationary data with time-invariant system matrices and classical assumptions, while permitting missing data.

## Usage

```
DFM(
  X,
  r,
  p = 1L,
```

```

  ...,
  idio.ar1 = FALSE,
  quarterly.vars = NULL,
  rQ = c("none", "diagonal", "identity"),
  rR = c("diagonal", "identity", "none"),
  em.method = c("auto", "DGR", "BM", "none"),
  min.iter = 25L,
  max.iter = 100L,
  tol = 1e-04,
  pos.corr = TRUE,
  check.increased = FALSE,
  save.full.state = TRUE
)

```

## Arguments

<code>X</code>	a $T \times n$ numeric data matrix or frame of stationary time series. May contain missing values. <i>Note</i> that data is internally standardized (scaled and centered) before estimation.
<code>r</code>	integer. Number of factors.
<code>p</code>	integer. Number of lags in factor VAR.
<code>...</code>	(optional) arguments to <code>tsnarmimp</code> . The default settings impute internal missing values with a cubic spline and the edges with the median and a 3-period moving average.
<code>idio.ar1</code>	logical. Model observation errors as AR(1) processes: $e_t = \rho e_{t-1} + v_t$ . <i>Note</i> that this substantially increases computation time, and is generally not needed if $n$ is large ( $>30$ ). See theoretical vignette for details.
<code>quarterly.vars</code>	character. Names of quarterly variables in <code>X</code> (if any). Monthly variables should be to the left of the quarterly variables in the data matrix and quarterly observations should be provided every 3rd period.
<code>rQ</code>	character. Restrictions on the state (transition) covariance matrix (Q).
<code>rR</code>	character. Restrictions on the observation (measurement) covariance matrix (R).
<code>em.method</code>	character. The implementation of the Expectation Maximization Algorithm used. The options are:
<code>"auto"</code>	Automatic selection: "BM" if <code>anyNA(X)</code> , else "DGR".
<code>"DGR"</code>	The classical EM implementation of Doz, Giannone and Reichlin (2012). This implementation is efficient and qu
<code>"BM"</code>	The modified EM algorithm of Banbura and Modugno (2014) which also accounts for missing data in the EM ite
<code>"none"</code>	Performs no EM iterations and just returns the Two-Step estimates from running the data through the Kalman Fil
<code>min.iter</code>	integer. Minimum number of EM iterations (to ensure a convergence path).

max. iter	integer. Maximum number of EM iterations.
tol	numeric. EM convergence tolerance.
pos.corr	logical. Increase the likelihood that factors correlate positively with the data, by scaling the eigenvectors such that the principal components (used to initialize the Kalman Filter) co-vary positively with the row-means of the standardized data.
check.increased	logical. Check if likelihood has increased. Passed to <code>em_converged</code> . If TRUE, the algorithm only terminates if convergence was reached with decreasing likelihood.
save.full.state	logical. Save full state-space matrices and smoothed states in <code>ss_full?</code> Set to FALSE to reduce object size.

## Details

This function efficiently estimates a Dynamic Factor Model with the following classical assumptions:

1. Linearity
2. Idiosyncratic measurement (observation) errors ( $R$  is diagonal)
3. No direct relationship between series and lagged factors (*ceteris paribus* contemporaneous factors)
4. No relationship between lagged error terms in the either measurement or transition equation (no serial correlation), unless explicitly modeled as AR(1) processes using `idio.ar1` = TRUE.

Factors are allowed to evolve in a  $VAR(p)$  process, and data is internally standardized (scaled and centered) before estimation (removing the need of intercept terms). By assumptions 1-4, this translates into the following dynamic form:

$$\begin{aligned}\mathbf{x}_t &= \mathbf{C}_0 \mathbf{f}_t + \mathbf{e}_t \sim N(\mathbf{0}, \mathbf{R}) \\ \mathbf{f}_t &= \sum_{j=1}^p \mathbf{A}_j \mathbf{f}_{t-j} + \mathbf{u}_t \sim N(\mathbf{0}, \mathbf{Q}_0)\end{aligned}$$

where the first equation is called the measurement or observation equation and the second equation is called transition, state or process equation, and

$n$	number of series in $\mathbf{x}_t$ ( $r$ and $p$ as the arguments to DFM).
$\mathbf{x}_t$	$n \times 1$ vector of observed series at time $t$ : $(x_{1t}, \dots, x_{nt})'$ . Some observations can be missing.
$\mathbf{f}_t$	$r \times 1$ vector of factors at time $t$ : $(f_{1t}, \dots, f_{rt})'$ .
$\mathbf{C}_0$	$n \times r$ measurement (observation) matrix.
$\mathbf{A}_j$	$r \times r$ state transition matrix at lag $j$ .

**Q<sub>0</sub>**  $r \times r$  state covariance matrix.

**R**  $n \times n$  measurement (observation) covariance matrix. It is diagonal by assumption 2 that  $E[\mathbf{x}_{it} | \mathbf{x}_{-i,t}, \mathbf{x}_{i,t-1}, \dots, \mathbf{f}_t, \mathbf{f}_{t-1}] = \mathbf{0}$ .

This model can be estimated using a classical form of the Kalman Filter and the Expectation Maximization (EM) algorithm, after transforming it to State-Space (stacked, VAR(1)) form:

$$\mathbf{x}_t = \mathbf{C}\mathbf{F}_t + \mathbf{e}_t \sim N(\mathbf{0}, \mathbf{R})$$

$$\mathbf{F}_t = \mathbf{A}\mathbf{F}_{t-1} + \mathbf{u}_t \sim N(\mathbf{0}, \mathbf{Q})$$

where

**n** number of series in  $\mathbf{x}_t$  ( $r$  and  $p$  as the arguments to DFM).

**x<sub>t</sub>**  $n \times 1$  vector of observed series at time  $t$ :  $(x_{1t}, \dots, x_{nt})'$ . Some observations can be missing.

**F<sub>t</sub>**  $rp \times 1$  vector of stacked factors at time  $t$ :  $(f_{1t}, \dots, f_{rt}, f_{1,t-1}, \dots, f_{r,t-1}, \dots, f_{1,t-p}, \dots, f_{r,t-p})'$ .

**C**  $n \times rp$  observation matrix. Only the first  $n \times r$  terms are non-zero, by assumption 3 that  $E[\mathbf{x}_t | \mathbf{F}_t] = E[\mathbf{x}_t | \mathbf{f}_t]$  (no relationship between  $\mathbf{x}_t$  and  $\mathbf{F}_{t-1}$ ).

**A** stacked  $rp \times rp$  state transition matrix consisting of 3 parts: the top  $r \times rp$  part provides the dynamic relationships between  $\mathbf{F}_t$  and  $\mathbf{F}_{t-1}$ .

**Q**  $rp \times rp$  state covariance matrix. The top  $r \times r$  part gives the contemporaneous relationships, the rest are zeros by assumption 3.

**R**  $n \times n$  observation covariance matrix. It is diagonal by assumption 2 and identical to **R** as stated in the dynamic form.

The filter is initialized with PCA estimates on the imputed dataset—see [SKFS](#) for a complete code example.

When modeling observations errors as AR(1) processes (`idio.ar1 = TRUE`) and/or when quarterly variables are included (`quarterly.vars = c(...)`), the state-space form of the model is augmented in order to estimate the additional parameters and apply appropriate restrictions - see the [theoretical vignette](#) for details. But `DFM()` returns matrices for the classical form of the factor model, and thus these modifications do not affect the output format.

## Value

A list-like object of class 'dfm' with the following elements:

**X\_imp**  $T \times n$  matrix with the imputed and standardized (scaled and centered) data—after applying `tsnarmimp`. It has attributes attached allowing for reconstruction of the original data:

"stats"	is a $n \times 5$ matrix of summary statistics of class "qsu" (see <a href="#">qsu</a> ).
"missing"	is a $T \times n$ logical matrix indicating missing or infinite values in the original data (which are imputed in $X_{imp}$ ).
"attributes"	contains the <a href="#">attributes</a> of the original data input.
"is.list"	is a logical value indicating whether the original data input was a list / data frame.
eigen	<code>eigen(cov(X_imp))</code> .
F_pca	$T \times r$ matrix of principal component factor estimates - $X_{imp} \%*% eigen\$vectors$ .
P_0	$r \times r$ initial factor covariance matrix estimate based on PCA results.
F_2s	$T \times r$ matrix two-step factor estimates as in Doz, Giannone and Reichlin (2011) - obtained from running the data through the Kalman Filter and Smoother once, where the Filter is initialized with results from PCA.
P_2s	$r \times r \times T$ covariance matrices of two-step factor estimates.
F_qml	$T \times r$ matrix of quasi-maximum likelihood factor estimates - obtained by iteratively Kalman Filtering and Smoothing the factor estimates until EM convergence.
P_qml	$r \times r \times T$ covariance matrices of QML factor estimates.
A	$r \times rp$ factor transition matrix.
C	$n \times r$ observation matrix.
Q	$r \times r$ state (error) covariance matrix.
R	$n \times n$ observation (error) covariance matrix.
ss_full	list of full state-space matrices and full-state smoothing results used internally (A, C, Q, R, F_0, P_0, F_smooth, P_smooth). Only stored when <code>save.full.state = TRUE</code> .
e	$T \times n$ estimates of observation errors $e_t$ . Only available if <code>idio.ar1 = TRUE</code> .
rho	$n \times 1$ estimates of AR(1) coefficients ( $\rho$ ) in observation errors: $e_t = \rho e_{t-1} + v_t$ . Only available if <code>idio.ar1 = TRUE</code> .
loglik	vector of log-likelihoods - one for each EM iteration. The final value corresponds to the log-likelihood of the reported model.
tol	The numeric convergence tolerance used.
converged	single logical valued indicating whether the EM algorithm converged (within <code>max.iter</code> iterations subject to <code>tol</code> ).
anyNA	single logical valued indicating whether there were any (internal) missing values in the data (determined after removal of rows with too many missing values). If FALSE, $X_{imp}$ is simply the original data in matrix form, and does not have the "missing" attribute attached.
rm.rows	vector of any cases (rows) that were removed beforehand (subject to <code>max.missing</code> and <code>na.rm.method</code> ). If no cases were removed the slot is NULL.
quarterly.vars	names of the quarterly variables (if any).
em.method	The EM method used.
call	call object obtained from <code>match.call()</code> .

## References

Doz, C., Giannone, D., & Reichlin, L. (2011). A two-step estimator for large approximate dynamic factor models based on Kalman filtering. *Journal of Econometrics*, 164(1), 188-205.

Doz, C., Giannone, D., & Reichlin, L. (2012). A quasi-maximum likelihood approach for large, approximate dynamic factor models. *Review of Economics and Statistics*, 94(4), 1014-1024.

Banbura, M., & Modugno, M. (2014). Maximum likelihood estimation of factor models on datasets with arbitrary pattern of missing data. *Journal of Applied Econometrics*, 29(1), 133-160.

Stock, J. H., & Watson, M. W. (2016). Dynamic Factor Models, Factor-Augmented Vector Autoregressions, and Structural Vector Autoregressions in Macroeconomics. *Handbook of Macroeconomics*, 2, 415–525. <https://doi.org/10.1016/bs.hesmac.2016.04.002>

## See Also

[dfms-package](#)

## Examples

```
library(magrittr)
library(xts)
library(vars)

# BM14 Replication Data. Constructing the database:
BM14 <- merge(BM14_M, BM14_Q)
BM14[, BM14_Models$log_trans] %>% log()
BM14[, BM14_Models$freq == "M"] %>% diff()
BM14[, BM14_Models$freq == "Q"] %>% diff(3)

### Small Model ----

# IC for number of factors
IC_small <- IC(BM14[, BM14_Models$small], max.r = 5)
plot(IC_small)
screepplot(IC_small)

# I take 2 factors. Now number of lags
VARselect(IC_small$F_pca[, 1:2])

# Estimating the model with 2 factors and 3 lags
dfm_small <- DFM(BM14[, BM14_Models$small], r = 2, p = 3,
                  quarterly.vars = BM14_Models %$% series[freq == "Q" & small])

# Inspecting the model
summary(dfm_small)
plot(dfm_small) # Factors and data
plot(dfm_small, method = "all", type = "individual") # Factor estimates
plot(dfm_small, type = "residual") # Residuals from factor predictions

# 10 periods ahead forecast
plot(predict(dfm_small), xlim = c(300, 370))
```

```

#### Medium-Sized Model ----

# IC for number of factors
IC_medium <- ICr(BM14[, BM14_Models$medium])
plot(IC_medium)
screenplot(IC_medium)

# I take 3 factors. Now number of lags
VARselect(IC_medium$F_pca[, 1:3])

# Estimating the model with 3 factors and 3 lags
dfm_medium <- DFM(BM14[, BM14_Models$medium], r = 3, p = 3,
                     quarterly.vars = BM14_Models %$% series[freq == "Q" & medium])

# Inspecting the model
summary(dfm_medium)
plot(dfm_medium) # Factors and data
plot(dfm_medium, method = "all", type = "individual") # Factor estimates
plot(dfm_medium, type = "residual") # Residuals from factor predictions

# 10 periods ahead forecast
plot(predict(dfm_medium), xlim = c(300, 370))

#### Large Model ----

# IC for number of factors
IC_large <- ICr(BM14)
plot(IC_large)
screenplot(IC_large)

# I take 6 factors. Now number of lags
VARselect(IC_large$F_pca[, 1:6])

# Estimating the model with 6 factors and 3 lags
dfm_large <- DFM(BM14, r = 6, p = 3,
                     quarterly.vars = BM14_Models %$% series[freq == "Q"])

# Inspecting the model
summary(dfm_large)
plot(dfm_large) # Factors and data
# plot(dfm_large, method = "all", type = "individual") # Factor estimates
plot(dfm_large, type = "residual") # Residuals from factor predictions

# 10 periods ahead forecast
plot(predict(dfm_large), xlim = c(300, 370))

#### Mixed-Frequency Model with AR(1) Idiosyncratic Errors ----

# Estimate model with AR(1) observation errors

```

```

# This models e(t) = rho * e(t-1) + v(t) for each series
dfm_large_ar1 <- DFM(BM14, r = 6, p = 3, idio.ar1 = TRUE,
quarterly.vars = BM14_Models %$% series[freq == "Q"])

# Model summary shows AR(1) coefficients
summary(dfm_large_ar1)

# Access AR(1) coefficients (rho) for each series
head(dfm_large_ar1$rho)

# Access estimated observation errors
head(dfm_large_ar1$e)

# Compare with model without AR(1) errors
dfm_large_ar1$loglik # Log-likelihood path

```

---

em\_converged

*Convergence Test for EM-Algorithm*

---

## Description

Convergence Test for EM-Algorithm

## Usage

```
em_converged(loglik, previous_loglik, tol = 1e-04, check.increased = FALSE)
```

## Arguments

loglik	numeric.	Current value of the log-likelihood function.
previous_loglik	numeric.	Value of the log-likelihood function at the previous iteration.
tol	numerical.	The tolerance of the test. If $ LL(t) - LL(t-1)  / avg < tol$ , where $avg = ( LL(t)  +  LL(t-1) )/2$ , then algorithm has converged.
check.increased	logical.	Check if likelihood has increased.

## Value

A logical statement indicating whether EM algorithm has converged. if `check.increased = TRUE`, a vector with 2 elements indicating the convergence status and whether the likelihood has decreased.

## See Also

[dfms-package](#)

## Examples

```
em_converged(1001, 1000)
em_converged(10001, 10000)
em_converged(10001, 10000, check = TRUE)
em_converged(10000, 10001, check = TRUE)
```

---

FIS

(Fast) Fixed-Interval Smoother (Kalman Smoother)

---

## Description

(Fast) Fixed-Interval Smoother (Kalman Smoother)

## Usage

```
FIS(A, F, F_pred, P, P_pred, F_0 = NULL, P_0 = NULL)
```

## Arguments

A	transition matrix ( $rp \times rp$ ).
F	state estimates ( $T \times rp$ ).
F_pred	state predicted estimates ( $T \times rp$ ).
P	variance estimates ( $rp \times rp \times T$ ).
P_pred	predicted variance estimates ( $rp \times rp \times T$ ).
F_0	initial state vector ( $rp \times 1$ ) or empty (NULL).
P_0	initial state covariance ( $rp \times rp$ ) or empty (NULL).

## Details

The Kalman Smoother is given by:

$$\begin{aligned}\mathbf{J}_t &= \mathbf{P}_t \mathbf{A} + \text{inv}(\mathbf{P}_{t+1}^{\text{pred}}) \\ \mathbf{F}_t^{\text{smooth}} &= \mathbf{F}_t + \mathbf{J}_t (\mathbf{F}_{t+1}^{\text{smooth}} - \mathbf{F}_{t+1}^{\text{pred}}) \\ \mathbf{P}_t^{\text{smooth}} &= \mathbf{P}_t + \mathbf{J}_t (\mathbf{P}_{t+1}^{\text{smooth}} - \mathbf{P}_{t+1}^{\text{pred}}) \mathbf{J}_t'\end{aligned}$$

The initial smoothed values for period  $t = T$  are set equal to the filtered values. If  $F_0$  and  $P_0$  are supplied, the smoothed initial conditions ( $t = 0$  values) are also calculated and returned. For further details see any textbook on time series such as Shumway & Stoffer (2017), which provide an analogous R implementation in `astsa::Ksmooth0`.

**Value**

Smoothed state and covariance estimates, including initial ( $t = 0$ ) values.

F_smooth	$T \times rp$ smoothed state vectors, equal to the filtered state in period $T$ .
P_smooth	$rp \times rp \times T$ smoothed state covariance, equal to the filtered covariance in period $T$ .
F_smooth_0	$1 \times rp$ initial smoothed state vectors, based on $F_0$ .
P_smooth_0	$rp \times rp$ initial smoothed state covariance, based on $P_0$ .

**References**

Shumway, R. H., & Stoffer, D. S. (2017). Time Series Analysis and Its Applications: With R Examples. Springer.

Harvey, A. C. (1990). Forecasting, structural time series models and the Kalman filter.

**See Also**

[SKF](#) [SKFS](#) [dfms-package](#)

**Examples**

```
# See ?SKFS
```

---

ICr

*Information Criteria to Determine the Number of Factors ( $r$ )*

---

**Description**

Minimizes 3 information criteria proposed by Bai and Ng (2002) to determine the optimal number of factors  $r^*$  to be used in an approximate factor model. A Screeplot can also be computed to eyeball the number of factors in the spirit of Onatski (2010).

**Usage**

```
ICr(X, max.r = min(20, ncol(X) - 1))

## S3 method for class 'ICr'
print(x, ...)

## S3 method for class 'ICr'
plot(x, ...)

## S3 method for class 'ICr'
screeplot(x, type = "pve", show.grid = TRUE, max.r = 30, ...)
```

## Arguments

X	a $T \times n$ numeric data matrix or frame of stationary time series.
max.r	integer. The maximum number of factors for which IC should be computed (or eigenvalues to be displayed in the screeplot).
x	an object of type 'ICr'.
...	further arguments to <code>ts.plot</code> or <code>plot</code> .
type	character. Either "ev" (eigenvalues), "pve" (percent variance explained), or "cum.pve" (cumulative PVE). Multiple plots can be requested.
show.grid	logical. TRUE shows gridlines in each plot.

## Details

Following Bai and Ng (2002) and De Valk et al. (2019), let  $NSSR(r)$  be the normalized sum of squared residuals  $SSR(r)/(n \times T)$  when  $r$  factors are estimated using principal components. Then the information criteria can be written as follows:

$$IC_{r1} = \ln(NSSR(r)) + r \left( \frac{n+T}{nT} \right) + \ln \left( \frac{nT}{n+T} \right)$$

$$IC_{r2} = \ln(NSSR(r)) + r \left( \frac{n+T}{nT} \right) + \ln(\min(n, T))$$

$$IC_{r3} = \ln(NSSR(r)) + r \left( \frac{\ln(\min(n, T))}{\min(n, T)} \right)$$

The optimal number of factors  $r^*$  corresponds to the minimum IC. The three criteria are asymptotically equivalent, but may give significantly different results for finite samples. The penalty in  $IC_{r2}$  is highest in finite samples.

In the Screeplot a horizontal dashed line is shown signifying an eigenvalue of 1, or a share of variance corresponding to 1 divided by the number of eigenvalues.

## Value

A list of 4 elements:

F_pca	$T \times n$ matrix of principle component factor estimates.
eigenvalues	the eigenvalues of the covariance matrix of X.
IC	$r.max \times 3$ 'table' containing the 3 information criteria of Bai and Ng (2002), computed for all values of $r$ from $1:r.max$ .
r.star	vector of length 3 containing the number of factors ( $r$ ) minimizing each information criterion.

## Note

To determine the number of lags (p) in the factor transition equation, use the function `vars::VARselect` with  $r^*$  principle components (also returned by `ICr`).

## References

Bai, J., Ng, S. (2002). Determining the Number of Factors in Approximate Factor Models. *Econometrica*, 70(1), 191-221. <https://doi.org/10.1111/1468-0262.00273>.

Onatski, A. (2010). Determining the number of factors from empirical distribution of eigenvalues. *The Review of Economics and Statistics*, 92(4), 1004-1016.

De Valk, S., de Mattos, D., & Ferreira, P. (2019). Nowcasting: An R package for predicting economic variables using dynamic factor models. *The R Journal*, 11(1), 230-244.

## See Also

[dfms-package](#)

## Examples

```
library(xts)
library(vars)

ics <- ICr(diff(BM14_M))
print(ics)
plot(ics)
screeplot(ics)

# Optimal lag-order with 6 factors chosen
VARselect(ics$F_pca[, 1:6])
```

---

## Description

Compute the Banbura and Modugno (2014) news decomposition of forecast updates. Given an old vintage and an updated vintage, the function decomposes the forecast revision at `t.fcst` into contributions from new releases.

## Usage

```
news(object, ...)

## S3 method for class 'dfm'
news(
  object,
  comparison,
  t.fcst = nrow(object$X_imp),
  target.vars = NULL,
  series = NULL,
  standardized = FALSE,
```

```

  ...
)

## S3 method for class 'dfm_news'
print(x, digits = 4L, ...)

## S3 method for class 'dfm_news_list'
print(x, digits = 4L, ...)

## S3 method for class 'dfm_news_list'
x$name

## S3 method for class 'dfm_news_list'
x[[i]]

## S3 method for class 'dfm_news_list'
x[i]

## S3 method for class 'dfm_news_list'
as.data.frame(x, ...)

```

## Arguments

object	a <code>dfm</code> object for the old vintage.
...	not used.
comparison	a <code>dfm</code> object or a new dataset for the updated vintage.
<code>t.fcst</code>	integer. Forecast target time index.
<code>target.vars</code>	Integer or character identifying target variables. Defaults to all variables.
<code>series</code>	optional character vector for naming variables.
<code>standardized</code>	logical. Return results on standardized scale?
<code>x</code>	an object of class <code>'dfm_news'</code> or <code>'dfm_news_list'</code> .
<code>digits</code>	integer. Number of digits to print.
<code>name</code>	character. Element name.
<code>i</code>	index. Element position or name.

## Details

Let  $y_t^{old}$  and  $y_t^{new}$  be the old and new forecasts of a target series at  $t = t_{fcst}$ . For each new release  $i$  (a previously missing observation that becomes observed), the innovation is

$$\nu_i = x_i^{new} - \hat{x}_i^{old},$$

where  $\hat{x}_i^{old}$  is the smoothed estimate from the old vintage. The revision is decomposed as

$$y_t^{new} - y_t^{old} = \sum_i g_i \nu_i,$$

with gain weights computed from Kalman smoother covariances:

$$g = \sigma_y C_y P_1 P_2^{-1}.$$

Here  $\sigma_y$  is the target series standard deviation,  $C_y$  is the loading row for the target series,  $P_1$  collects cross-covariances between the target and each news item, and  $P_2$  is the covariance matrix of the news items (including measurement error where appropriate). See Section 2.3 and Appendix D in Banbura and Modugno (2014).

The function uses the system matrices and scaling from the new vintage. The old data are re-standardized to the new-vintage scale before smoothing so that innovations and gains are computed on a consistent scale. Set `standardized = FALSE` to report results on the original data scale.

### Value

For a single target, a `dfm_news` object with elements:

- `y_old`: old forecast for the target variable at `t.fcst`.
- `y_new`: new forecast for the target variable at `t.fcst`.
- `news_df`: data frame with one row per series and columns:
  - `series`: series name.
  - `actual`: actual release (if any).
  - `forecast`: old-vintage forecast of the release.
  - `news`: total innovation for the series on the output scale. If there is a single release, `news` equals `actual - forecast`. With multiple releases, `news` aggregates those innovations for the series.
  - `gain`: effective weight on `news` such that `impact = news * gain` (on the output scale).
  - `gain_std`: effective weight on the standardized innovations.
  - `impact`: contribution of the series to the target revision.

If `target.vars` selects multiple targets, a `dfm_news_list` object is returned, where each element is a `dfm_news` object and list names correspond to targets.

### Note

This implementation is translated from the original MATLAB codes and is consistent with the BM2014 news decomposition formulas. If the model was estimated with `max.missing < 1` and `na.rm.method = "LE"` in `tsnarmimp` (called by `DFM()`), leading or trailing rows with many missing values may be removed by `DFM()`. If old and new vintages are both `dfm` objects, and they drop different rows, then `t.fcst` can become out of bounds. When comparison is provided as raw data, `news()` drops `object$rm.rows` from the new dataset (if present) and forces `max.missing = 1` for the re-estimation call to keep row alignment. To avoid issues, estimate both vintages with `max.missing = 1`. For mixed-frequency or idiosyncratic AR(1) models, `news()` relies on the full state-space matrices stored in `dfm$ss_full`.

### References

Banbura, M., & Modugno, M. (2014). Maximum likelihood estimation of factor models on datasets with arbitrary pattern of missing data. *Journal of Applied Econometrics*, 29(1), 133-160.

**See Also**[dfms-package](#)**Examples**

```

# (1) Monthly DFM example
X <- collapse::qM(BM14_M)[, BM14_Models$medium[BM14_Models$freq == "M"]]
X_old <- X
# Creating earlier vintage
X_old[nrow(X) - 1, sample(which(is.finite(X[nrow(X) - 1, ]) & is.na(X[nrow(X), ])), 5)] <- NA
X_old[nrow(X), sample(which(is.finite(X[nrow(X), ])), 5)] <- NA
# Estimating DFM
dfm <- DFM(X_old, r = 2, p = 2, em.method = "none")
# News computation (second DFM fit internally with same settings and rows)
res <- news(dfm, X, target.vars = c("ip_tot_cstr", "orders", "urx"))
# See results
print(res)
head(res$news_df)

# (2) MQ nowcast of GDP (idio.ar1 = FALSE for speed)
library(magrittr)
library(xts)
# Creating MQ dataset
BM14 <- merge(BM14_M, BM14_Q)
BM14[, BM14_Models$log_trans] %>% log()
BM14[, BM14_Models$freq == "M"] %>% diff()
BM14[, BM14_Models$freq == "Q"] %>% diff(3)
X <- BM14[-1, BM14_Models$small]
quarterly.vars <- BM14_Models$series[BM14_Models$small & BM14_Models$freq == "Q"]
# Creating earlier vintage
X_old <- X
X_old[355, "ip_tot_cstr"] <- NA
X_old[355, "new_cars"] <- NA
X_old[356, "new_cars"] <- NA
X_old[356, "pms_pmi"] <- NA
X_old[356, "euro325"] <- NA
X_old[356, "capacity"] <- NA
# Estimating DFM
dfm <- DFM(X_old, r = 2, p = 2, quarterly.vars = quarterly.vars, max.missing = 1)
# News computation (second DFM fit internally with same settings and rows)
res_mq <- news(dfm, X, t.fcst = 356, target.vars = "gdp")
# See results
print(res_mq)
head(res_mq$news_df)

```

## Description

Plot DFM

## Usage

```
## S3 method for class 'dfm'
plot(
  x,
  method = switch(x$em.method, none = "2s", "qml"),
  type = c("joint", "individual", "residual"),
  scale.factors = TRUE,
  ...
)

## S3 method for class 'dfm'
screeplot(x, ...)
```

## Arguments

x	an object class 'dfm'.
method	character. The factor estimates to use: one of "qml", "2s", "pca" or "all" to plot all estimates.
type	character. The type of plot: "joint", "individual" or "residual".
scale.factors	logical. Standardize factor estimates, this usually improves the plot since the factor estimates corresponding to the greatest PCA eigenvalues tend to have a greater variance than the data.
...	for plot.dfm: further arguments to <a href="#">plot</a> , <a href="#">ts.plot</a> , or <a href="#">boxplot</a> , depending on the type of plot. For screeplot.dfm: further arguments to <a href="#">screeplot.ICr</a> .

## Value

Nothing.

## See Also

[dfms-package](#)

## Examples

```
# Fit DFM with 3 factors and 3 lags in the transition equation
mod <- DFM(diff(BM14_M), r = 3, p = 3)
plot(mod)
plot(mod, type = "individual", method = "all")
plot(mod, type = "residual")
```

predict.dfm

*DFM Forecasts***Description**

This function produces h-step ahead forecasts of both the factors and the data, with an option to also forecast autocorrelated residuals with a univariate method and produce a combined forecast.

**Usage**

```
## S3 method for class 'dfm'
predict(
  object,
  h = 10L,
  method = switch(object$em.method, none = "2s", "qml"),
  standardized = TRUE,
  use.full.state = TRUE,
  resFUN = NULL,
  resAC = 0.1,
  ...
)

## S3 method for class 'dfm_forecast'
print(x, digits = 4L, ...)

## S3 method for class 'dfm_forecast'
plot(
  x,
  main = paste(x$h, "Period Ahead DFM Forecast"),
  xlab = "Time",
  ylab = "Standardized Data",
  factors = seq_len(ncol(x$F)),
  scale.factors = TRUE,
  factor.col = rainbow(length(factors)),
  factor.lwd = 1.5,
  fcst.lty = "dashed",
  data.col = c("grey85", "grey65"),
  legend = TRUE,
  legend.items = paste0("f", factors),
  grid = FALSE,
  vline = TRUE,
  vline.lty = "dotted",
  vline.col = "black",
  ...
)

## S3 method for class 'dfm_forecast'
```

```
as.data.frame(
  x,
  ...,
  use = c("factors", "data", "both"),
  pivot = c("long", "wide"),
  time = seq_len(nrow(x$F) + x$h),
  stringsAsFactors = TRUE
)
```

## Arguments

object	an object of class 'dfm'.
h	integer. The forecast horizon.
method	character. The factor estimates to use: one of "qml", "2s" or "pca".
standardized	logical. FALSE will return data forecasts on the original scale.
use.full.state	logical. Use the full state-space (if available) when computing residuals for optional residual forecasting. When <code>idio.ar1</code> = TRUE, this yields residuals after both factor and idiosyncratic components; set to FALSE to use factor-only residuals. Falls back to the compact form if unavailable or if <code>method</code> = "pca".
resFUN	an (optional) function to compute a univariate forecast of the residuals. The function needs to have a second argument providing the forecast horizon (h) and return a vector of forecasts. See Examples.
resAC	numeric. Threshold for residual autocorrelation to apply <code>resFUN</code> : only residual series where $AC1 > resAC$ will be forecasted.
...	not used.
x	an object class 'dfm_forecast'.
digits	integer. The number of digits to print out.
main, xlab, ylab	character. Graphical parameters passed to <code>ts.plot</code> .
factors	integers indicating which factors to display. Setting this to NA, NULL or 0 will omit factor plots.
scale.factors	logical. Standardize factor estimates, this usually improves the plot since the factor estimates corresponding to the greatest PCA eigenvalues tend to have a greater variance than the data.
factor.col, factor.lwd	graphical parameters affecting the colour and line width of factor estimates plots. See <code>par</code> .
fcst.lty	integer or character giving the line type of the forecasts of factors and data. See <code>par</code> .
data.col	character vector of length 2 indicating the colours of historical data and forecasts of that data. Setting this to NA, NULL or "" will not plot data and data forecasts.
legend	logical. TRUE draws a legend in the top-left of the chart.
legend.items	character names of factors for the legend.
grid	logical. TRUE draws a grid on the background of the plot.

vline logical. TRUE draws a vertical line delimiting historical data and forecasts.  
 vline.lty, vline.col graphical parameters affecting the appearance of the vertical line. See [par](#).  
 use character. Which forecasts to use "factors", "data" or "both".  
 pivot character. The orientation of the frame: "long" or "wide".  
 time a vector identifying the time dimension, must be of length  $T + h$ , or NULL to omit a time variable.  
 stringsAsFactors logical. If TRUE and pivot = "long" the 'Variable' column is created as a factor. Same as option to [as.data.frame.table](#).

## Value

A list-like object of class 'dfm\_forecast' with the following elements:

X\_fcst  $h \times n$  matrix with the forecasts of the variables.  
 F\_fcst  $h \times r$  matrix with the factor forecasts.  
 X  $T \times n$  matrix with the standardized (scaled and centered) data - with attributes attached allowing reconstruction of the original data:  
 "stats" is a  $n \times 5$  matrix of summary statistics of class "qsu" (see [qsu](#)). Only attached if `standardized = TRUE`.  
 "attributes" contains the [attributes](#) of the original data input.  
 "is.list" is a logical value indicating whether the original data input was a list / data frame.

F  $T \times r$  matrix of factor estimates.  
 method the factor estimation method used.  
 anyNA logical indicating whether X contains any missing values.  
 h the forecast horizon.  
 resid.fc logical indicating whether a univariate forecasting function was applied to the residuals.  
 resid.fc.ind indices indicating for which variables (columns of X) the residuals were forecasted using the univariate function.  
 call call object obtained from `match.call()`.

## See Also

[dfms-package](#)

## Examples

```

library(xts)
library(collapse)

# Fit DFM with 3 factors and 3 lags in the transition equation
mod <- DFM(diff(BM14_M), r = 3, p = 3)

# 15 period ahead forecast
fc <- predict(mod, h = 15)
print(fc)
plot(fc, xlim = c(300, 370))

# Also forecasting autocorrelated residuals with an AR(1)
fcfun <- function(x, h) predict(ar(na_rm(x)), n.ahead = h)$pred
fcar <- predict(mod, resFUN = fcfun, h = 15)
plot(fcar, xlim = c(300, 370))

# Retrieving a data frame of the forecasts
head(as.data.frame(fcar, pivot = "wide")) # Factors
head(as.data.frame(fcar, use = "data")) # Data
head(as.data.frame(fcar, use = "both")) # Both

```

---

residuals.dfm

*DFM Residuals and Fitted Values*

---

## Description

The residuals  $\mathbf{e}_t = \mathbf{x}_t - \mathbf{CF}_t$  or fitted values  $\mathbf{CF}_t$  of the DFM observation equation.

## Usage

```

## S3 method for class 'dfm'
residuals(
  object,
  method = switch(object$em.method, none = "2s", "qml"),
  orig.format = FALSE,
  standardized = FALSE,
  na.keep = TRUE,
  use.full.state = TRUE,
  ...
)

## S3 method for class 'dfm'
fitted(
  object,
  method = switch(object$em.method, none = "2s", "qml"),
  orig.format = FALSE,

```

```

  standardized = FALSE,
  na.keep = TRUE,
  use.full.state = TRUE,
  ...
)

```

### Arguments

object	an object of class 'dfm'.
method	character. The factor estimates to use: one of "qml", "2s" or "pca".
orig.format	logical. TRUE returns residuals/fitted values in a data format similar to X.
standardized	logical. FALSE will put residuals/fitted values on the original data scale.
na.keep	logical. TRUE inserts missing values where X is missing (default TRUE as residuals/fitted values are only defined for observed data). FALSE returns the raw prediction, which can be used to interpolate data based on the DFM. For residuals, FALSE returns the difference between the prediction and the initial imputed version of X use for PCA to initialize the Kalman Filter.
use.full.state	logical. Use the full state-space (if available) for fitted values and residuals. This includes idiosyncratic state components when idio.ar1 = TRUE, so fitted values reflect the full observation equation and residuals measure what is left after both factor and idiosyncratic components. Set to FALSE to obtain factor-only fitted values and residuals. Falls back to the compact form if unavailable or if method = "pca".
...	not used.

### Value

A matrix of DFM residuals or fitted values. If orig.format = TRUE the format may be different, e.g. a data frame.

### See Also

[dfms-package](#)

### Examples

```

library(xts)
# Fit DFM with 3 factors and 3 lags in the transition equation
mod <- DFM(diff(BM14_M), r = 3, p = 3)

# Residuals
head(resid(mod))
plot(resid(mod, orig.format = TRUE)) # this is an xts object

# Fitted values
head(fitted(mod))
head(fitted(mod, orig.format = TRUE)) # this is an xts object

```

---

SKF	<i>(Fast) Stationary Kalman Filter</i>
-----	--

---

## Description

A simple and fast C++ implementation of the Kalman Filter for stationary data (or random walks  
- data should be mean zero and without a trend) with time-invariant system matrices and missing data.

## Usage

```
SKF(X, A, C, Q, R, F_0, P_0, loglik = FALSE)
```

## Arguments

X	numeric data matrix ( $T \times n$ ).
A	transition matrix ( $rp \times rp$ ).
C	observation matrix ( $n \times rp$ ).
Q	state covariance ( $rp \times rp$ ).
R	observation covariance ( $n \times n$ ).
F_0	initial state vector ( $rp \times 1$ ).
P_0	initial state covariance ( $rp \times rp$ ).
loglik	logical. Compute log-likelihood?

## Details

The underlying state space model is:

$$\mathbf{x}_t = \mathbf{C}\mathbf{F}_t + \mathbf{e}_t \sim N(\mathbf{0}, \mathbf{R})$$

$$\mathbf{F}_t = \mathbf{A}\mathbf{F}_{t-1} + \mathbf{u}_t \sim N(\mathbf{0}, \mathbf{Q})$$

where  $x_t$  is  $X[t, :]$ . The filter then first performs a time update (prediction)

$$\mathbf{F}_t = \mathbf{A}\mathbf{F}_{t-1}$$

$$\mathbf{P}_t = \mathbf{A}\mathbf{P}_{t-1}\mathbf{A}' + \mathbf{Q}$$

where  $P_t = Cov(F_t)$ . This is followed by the measurement update (filtering)

$$\mathbf{K}_t = \mathbf{P}_t \mathbf{C}' (\mathbf{C}\mathbf{P}_t \mathbf{C}' + \mathbf{R})^{-1}$$

$$\mathbf{F}_t = \mathbf{F}_t + \mathbf{K}_t (\mathbf{x}_t - \mathbf{C}\mathbf{F}_t)$$

$$\mathbf{P}_t = \mathbf{P}_t - \mathbf{K}_t \mathbf{C} \mathbf{P}_t$$

If a row of the data is all missing the measurement update is skipped i.e. the prediction becomes the filtered value. The log-likelihood is computed as

$$1/2 \sum_t \log(|S_t|) - e_t' S_t e_t - n \log(2\pi)$$

where  $S_t = (C P_t C' + R)^{-1}$  and  $e_t = x_t - C F_t$  is the prediction error.

For further details see any textbook on time series such as Shumway & Stoffer (2017), which provide an analogous R implementation in `astsa::Kfilter0`. For another fast (C-based) implementation that also allows time-varying system matrices and non-stationary data see `FKF::fkf`.

### Value

Predicted and filtered state vectors and covariances.

<code>F</code>	$T \times rp$ filtered state vectors.
<code>P</code>	$rp \times rp \times T$ filtered state covariances.
<code>F_pred</code>	$T \times rp$ predicted state vectors.
<code>P_pred</code>	$rp \times rp \times T$ predicted state covariances.
<code>loglik</code>	value of the log likelihood.

### References

Shumway, R. H., & Stoffer, D. S. (2017). *Time Series Analysis and Its Applications: With R Examples*. Springer.

Harvey, A. C. (1990). Forecasting, structural time series models and the Kalman filter.

Hamilton, J. D. (1994). *Time Series Analysis*. Princeton university press.

### See Also

[FIS](#) [SKFS](#) [dfms-package](#)

### Examples

```
# See ?SKFS
```

---

SKFS

*(Fast) Stationary Kalman Filter and Smoother*

---

### Description

(Fast) Stationary Kalman Filter and Smoother

### Usage

```
SKFS(X, A, C, Q, R, F_0, P_0, loglik = FALSE)
```

## Arguments

X	numeric data matrix ( $T \times n$ ).
A	transition matrix ( $rp \times rp$ ).
C	observation matrix ( $n \times rp$ ).
Q	state covariance ( $rp \times rp$ ).
R	observation covariance ( $n \times n$ ).
F_0	initial state vector ( $rp \times 1$ ).
P_0	initial state covariance ( $rp \times rp$ ).
loglik	logical. Compute log-likelihood?

## Value

All results from [SKF](#) and [FIS](#), and additionally a  $rp \times rp \times T$  matrix `PPm_smooth`, which is equal to the estimate of  $Cov(F_t^{smooth}, F_{t-1}^{smooth} | T)$  and needed for EM iterations. See 'Property 6.3: The Lag-One Covariance Smoother' in Shumway & Stoffer (2017).

## References

Shumway, R. H., & Stoffer, D. S. (2017). Time Series Analysis and Its Applications: With R Examples. Springer.

## See Also

[SKF](#) [FIS](#) [dfms-package](#)

## Examples

```
library(collapse)

## Two-Step factor estimates from monthly BM (2014) data
X <- fscale(diff(qM(BM14_M))) # Standardizing as KF has no intercept
r <- 5L # 5 Factors
p <- 3L # 3 Lags
n <- ncol(X)

## Initializing the Kalman Filter with PCA results
X_imp <- tsnarmimp(X) # Imputing Data
v <- eigen(cov(X_imp))$vectors[, 1:r] # PCA
F_pc <- X_imp %*% v # Principal component factor estimates
C <- cbind(v, matrix(0, n, r*p-r)) # Observation matrix
res <- X - tcrossprod(F_pc, v) # Residuals from static predictions
R <- diag(fvar(res)) # Observation residual covariance
var <- .VAR(F_pc, p) # VAR(p)
A <- rbind(t(var$A), diag(1, r*p-r, r*p))
Q <- matrix(0, r*p, r*p) # VAR residual matrix
Q[1:r, 1:r] <- cov(var$res)
F_0 <- var$X[1L, ] # Initial factor estimate and covariance
P_0 <- ainv(diag((r*p)^2) - kronecker(A,A)) %*% unattrib(Q)
```

```

dim(P_0) <- c(r*p, r*p)

## Run standartized data through Kalman Filter and Smoother once
kfs_res <- SKFS(X, A, C, Q, R, F_0, P_0, FALSE)

## Two-step solution is state mean from the Kalman Smoother
F_kal <- kfs_res$F_smooth[, 1:r, drop = FALSE]
colnames(F_kal) <- paste0("f", 1:r)

## See that this is equal to the Two-Step estimate by DFM()
all.equal(F_kal, DFM(X, r, p, em.method = "none", pos.cor = FALSE)$F_2s)

## Same in two steps using SKF() and FIS()
kfs_res2 <- with(SKF(X, A, C, Q, R, F_0, P_0, FALSE), FIS(A, F, F_pred, P, P_pred))
F_kal2 <- kfs_res2$F_smooth[, 1:r, drop = FALSE]
colnames(F_kal2) <- paste0("f", 1:r)
all.equal(F_kal, F_kal2)

rm(X, r, p, n, X_imp, v, F_pc, C, res, R, var, A, Q, F_0, P_0, kfs_res, F_kal, kfs_res2, F_kal2)

```

---

## summary.dfm

### DFM Summary Methods

---

#### Description

Summary and print methods for class 'dfm'. `print.dfm` just prints basic model information and the factor transition matrix **A**, `coef.dfm` returns **A** and **C** in a plain list, whereas `summary.dfm` returns all system matrices and additional residual and goodness of fit statistics—with a print method allowing full or compact printout.

#### Usage

```

## S3 method for class 'dfm'
print(x, digits = 4L, ...)

## S3 method for class 'dfm'
coef(object, ...)

## S3 method for class 'dfm'
logLik(object, ...)

## S3 method for class 'dfm'
summary(object, method = switch(object$em.method, none = "2s", "qml"), ...)

## S3 method for class 'dfm_summary'
print(x, digits = 4L, compact = sum(x$info["n"] > 15, x$info["n"] > 40), ...)

```

## Arguments

x, object	an object class 'dfm'.
digits	integer. The number of digits to print out.
...	not used.
method	character. The factor estimates to use: one of "qml", "2s" or "pca".
compact	integer. Display a more compact printout: 0 prints everything, 1 omits the observation matrix $\mathbf{C}$ and residual covariance matrix $\text{cov}(\text{resid}(\text{model}))$ , and 2 omits all disaggregated information on the input data. Sensible default are chosen for different sizes of the input dataset so as to limit large printouts.

## Value

Summary information following a dynamic factor model estimation. `coef()` returns  $\mathbf{A}$  and  $\mathbf{C}$ .

## See Also

[dfms-package](#)

## Examples

```
mod <- DFM(diff(BM14_Q), 2, 3)
print(mod)
summary(mod)
```

---

tsnarmimp

*Remove and Impute Missing Values in a Multivariate Time Series*

---

## Description

This function imputes missing values in a stationary multivariate time series using various methods, and removes cases with too many missing values.

## Usage

```
tsnarmimp(
  X,
  max.missing = 0.8,
  na.rm.method = c("LE", "all"),
  na.impute = c("median.ma.spline", "median.ma", "median", "rnorm"),
  ma.terms = 3L
)
```

## Arguments

X	a $T \times n$ numeric data matrix (incl. ts or xts objects) or data frame of stationary time series.
max.missing	numeric. Proportion of series missing for a case to be considered missing.
na.rm.method	character. Method to apply concerning missing cases selected through max.missing: "LE" only removes cases at the beginning or end of the sample, whereas "all" always removes missing cases.
na.impute	character. Method to impute missing values for the PCA estimates used to initialize the EM algorithm. Note that data are standardized (scaled and centered) beforehand. Available options are:
"median"	simple series-wise median imputation.
"rnorm"	imputation with random numbers drawn from a standard normal distribution.
"median.ma"	values are initially imputed with the median, but then a moving average is applied to smooth the estimates.
"median.ma.spline"	"internal" missing values (not at the beginning or end of the sample) are imputed using a cubic spline.
ma.terms	the order of the (2-sided) moving average applied in na.impute methods "median.ma" and "median.ma.spline".

## Value

The imputed matrix X\_imp, with attributes:

"missing"	a missingness matrix W matching the dimensions of X_imp.
"rm.rows"	and a vector of indices of rows (cases) with too many missing values that were removed.

## See Also

[dfms-package](#)

## Examples

```
library(xts)
str(tsnarmimp(BM14_M))
```

# Index

\* **datasets**  
    BM14\_Models, 7  
    .VAR, 4  
    .VAR(), 4  
    [.dfm\_news\_list (news), 19  
    [[.dfm\_news\_list (news), 19  
    \$.dfm\_news\_list (news), 19  
  
    ainv, 5  
    ainv(), 4  
    apinv (ainv), 5  
    apinv(), 4  
    as.data.frame(<dfm>), 3  
    as.data.frame(<dfm\_forecast>), 3  
    as.data.frame(<dfm\_news\_list>), 3  
    as.data.frame.dfm, 6  
    as.data.frame.dfm\_forecast  
        (predict.dfm), 24  
    as.data.frame.dfm\_news\_list (news), 19  
    as.data.frame.table, 6, 26  
    attributes, 12, 26  
  
    BM14\_M, 4  
    BM14\_M (BM14\_Models), 7  
    BM14\_Models, 4, 7  
    BM14\_Q, 4  
    BM14\_Q (BM14\_Models), 7  
    boxplot, 23  
  
    coef.dfm (summary.dfm), 32  
  
    DFM, 8  
    DFM(), 3  
    dfms (dfms-package), 2  
    dfms-package, 2, 5, 6, 8, 13, 15, 17, 19, 22,  
        23, 26, 28, 30, 31, 33, 34  
  
    em\_converged, 10, 15  
    em\_converged(), 4  
  
    FIS, 16, 30, 31  
  
    FIS(), 3  
    fitted(<dfm>), 3  
    fitted.dfm (residuals.dfm), 27  
  
    ICr, 17  
    ICr(), 3  
  
    logLik.dfm (summary.dfm), 32  
  
    news, 19  
    news(<dfm>), 3  
  
    par, 25, 26  
    plot, 18, 23  
    plot(<dfm>), 3  
    plot(<dfm\_forecast>), 3  
    plot(<ICr>), 3  
    plot.dfm, 22  
    plot.dfm\_forecast (predict.dfm), 24  
    plot.ICr (ICr), 17  
    predict(<dfm>), 3  
    predict.dfm, 24  
    print.dfm (summary.dfm), 32  
    print.dfm\_forecast (predict.dfm), 24  
    print.dfm\_news (news), 19  
    print.dfm\_news\_list (news), 19  
    print.dfm\_summary (summary.dfm), 32  
    print.ICr (ICr), 17  
  
    qsu, 12, 26  
  
    resid.dfm (residuals.dfm), 27  
    residuals(<dfm>), 3  
    residuals.dfm, 27  
  
    screeplot(<ICr>), 3  
    screeplot.dfm (plot.dfm), 22  
    screeplot.ICr, 23  
    screeplot.ICr (ICr), 17  
    SKF, 17, 29, 31  
    SKF(), 3

SKFS, [11](#), [17](#), [30](#), [30](#)  
SKFS(), [3](#)  
summary(<dfm>), [3](#)  
summary.dfm, [32](#)  
  
ts.plot, [18](#), [23](#), [25](#)  
tsnarmimp, [9](#), [11](#), [21](#), [33](#)  
tsnarmimp(), [4](#)